

View Online at <https://aerobasegroup.com/nsn/5305-00-193-5231>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.201 inches and 0.283 inches

**Fastener Length:**

Between 0.296 inches and 0.328 inches

**Head Style:**

Flat countersunk

**Head Diameter:**

Between 0.177 inches and 0.225 inches

**Locking Feature:**

Patch threads

**Internal Drive Style:**

Cross recess type 1

**Thread Diameter:**

0.112 inches

**Thready Qty Per Inch (tpi):**

40

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

**Surface Finish:**

32.0 microinches threads

**Material:**

Iron alloy 660

**Material Specification:**

Ams 5731 assn standard single material response or ams 5737 assn standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Thread Series Designator:**

Unjc

**Specification Data:**

80205-nas1741 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0