## NSN 5305-00-193-6758

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-193-6758 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.219 inches **Fastener Length:** 1.375 inches **Head Style:** Fillister **Head Diameter:** Between 0.309 inches and 0.321 inches **Head Height:** Between 0.085 inches and 0.095 inches **First Diameter From Head:** Between 0.118 inches and 0.120 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 1.062 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.164 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 57000 pounds per square inch Minimum Yield Strength: 25000 pounds per square inch **Externally Relieved Body Diameter Quantity:** 1 Material: Copper alloy **Material Specification:** Qq-b-626 federal specification single material response **Surface Treatment:** Nickel **Surface Treatment Specification:** Qq-n-290 federal specification single treatment response **Thread Series Designator:** Unc Shelf Life:

N/a

## NSN 5305-00-193-6758

Externally Relieved Body Screw - Page 2 of 2



ш	ın	10	<i>(</i> )+	Measure:	

--

Demilitarization:

No

Fiig:

A003b0