Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-193-6758

Thread Class:
2a
Thread Direction:
Right-hand
Thread Length:
0.219 inches
Fastener Length:
1.375 inches
Head Style:
Fillister
Head Diameter:
Between 0.309 inches and 0.321 inches
Head Height:
Between 0.085 inches and 0.095 inches
First Diameter From Head:
Between 0.118 inches and 0.120 inches
Distance From Largest Bearing Surface Of Head To End Of First Diameter:
1.062 inches
Internal Drive Style:
Slot
Thread Diameter:
0.164 inches
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
57000 pounds per square inch
Minimum Yield Strength:
25000 pounds per square inch
Externally Relieved Body Diameter Quantity:
1
Material:
Copper alloy
Material Specification:
Qq-b-626 federal specification single material response
Surface Treatment:
Nickel
Surface Treatment Specification:
Qq-n-290 federal specification single treatment response
Thread Series Designator:
Unc
Shelf Life:
N/a

Externally Relieved Body Screw - Page 2 of 2



Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0