Assembled Washer Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-00-194-0768



# **Thread Class:** 2a

**Thread Direction:** 

**Right-hand** 

#### Thread Length:

Between 0.450 inches and 0.500 inches

#### Fastener Length:

0.500 inches

## Head Style:

Pan

#### Head Diameter:

Between 0.205 inches and 0.219 inches

#### **Head Height:**

Between 0.070 inches and 0.080 inches

#### Washer Quantity:

2

#### Internal Drive Style:

Cross recess type 1

#### Thread Diameter:

0.112 inches

#### Thready Qty Per Inch (tpi):

40

#### Hardness Rating:

45.0 rockwell c primary washer and 53.0 rockwell c primary washer

### Secondary Washer Relationship To Primary Washer:

Not identical

#### Secondary Washer Style:

Flat

#### Primary Washer Outside Diameter:

0.209 inches

#### Secondary Washer Outside Diameter:

Between 0.307 inches and 0.320 inches

#### **Primary Washer Style:**

Split helical ring

#### **Primary Washer Material Thickness:**

Between 0.025 inches and 0.031 inches

#### Secondary Washer Material Thickness:

Between 0.025 inches and 0.040 inches

#### Material Specification:

Astm-a576 assn standard all material responses fastener or astm-a108 assn standard all material responses fastener

#### Surface Treatment:

Cadmium and chromate

Assembled Washer Screw - Page 2 of 2



#### Surface Treatment Specification:

Qq-p-416, type 2, cl 3 federal specification single treatment response

#### Thread Series Designator:

Unc

Shelf Life:

N/a

## Unit Of Measure:

---

## Demilitarization:

No

Fiig:

A003b0