NSN 5305-00-194-6903

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-194-6903 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.332 inches and 0.399 inches **Fastener Length:** Between 2.030 inches and 2.077 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.625 inches and 0.635 inches **Grip Diameter:** Between 0.3108 inches and 0.3117 inches **Internal Drive Style:** Offset cruciform (torque set) **Thread Diameter:** 0.312 inches **Grip Length:** Between 1.678 inches and 1.698 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 300000 pounds per square inch Hardness Rating: 55.0 rockwell c and 58.0 rockwell c **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Surface Finish:** 32.0 microinches threads Material: Steel **Material Specification:** Vanadium vasco jet m-a fscm 87665 mfr ref single material response **Surface Treatment:** Nickel and cadmium **Surface Treatment Specification:** Ams 2416 assn standard all treatment responses **Thread Series Designator:** Unjf Shelf Life:

N/a

NSN 5305-00-194-6903

Close Tolerance Screw - Page 2 of 2



ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A003b0