# NSN 5305-00-195-0923

Panel Screw Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-195-0923

# Thread Class:

3a

**Thread Direction:** 

**Right-hand** 

# Thread Length:

0.497 inches

#### Fastener Length:

0.542 inches

#### Head Style:

Knurled no. 1

Head Diameter:

#### 0.451 inches

Head Height:

#### 0.290 inches

Internal Drive Style:

# Slot

#### End Application:

Lw/s: whidbey island class lsd; lpd-17 class amphibious transport dock; spruance class dd (963); guided missile system, ram ex43; missile, air launch cruise (alcm) agm-86b; wasp class lhd; defense support program

#### Material Accommodated Thickness:

Between 0.094 inches and 0.155 inches

# Thread Diameter:

0.190 inches

#### Thready Qty Per Inch (tpi):

32

#### Material:

Steel comp 302 spring

#### **Material Specification:**

Qq-w-423 cond b federal specification single material response spring

#### Surface Treatment:

Passivate spring

#### **Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response spring

#### Thread Series Designator:

Unf

Shelf Life:

N/a

### Unit Of Measure:

---

#### Demilitarization:

No

# Fiig:

A003b0

NSN 5305-00-195-0923

Panel Screw Assembly - Page 2 of 2

# Mil-std (military Standard):

Mil-a-8625 spec.

