

View Online at <https://aerobasegroup.com/nsn/5305-00-195-9595>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.271 inches and 0.281 inches

**Fastener Length:**

0.406 inches

**Head Style:**

Fillister

**Head Diameter:**

Between 0.166 inches and 0.183 inches

**Head Height:**

Between 0.072 inches and 0.079 inches

**First Diameter From Head:**

0.112 inches

**Second Diameter From Head:**

Between 0.081 inches and 0.084 inches

**Distance From Largest Bearing Surface Of Head To End Of First Diameter:**

Between 0.271 inches and 0.281 inches

**Distance From Largest Bearing Surface Of Head To End Of Second Diameter:**

0.406 inches

**Internal Drive Style:**

Slot

**Thread Diameter:**

0.112 inches

**Thready Qty Per Inch (tpi):**

40

**Min. Tensile Strength (psi):**

80000 pounds per square inch

**Externally Relieved Body Diameter Quantity:**

2

**Special Features:**

First diameter from head is threaded portion

**Material:**

Stainless steel

**Material Specification:**

66 federal standard single material response

**Surface Treatment:**

Passivate

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0