Externally Relieved Body Screw - Page 1 of 2

AeroBase Group

View Online at https://aerobasegroup.com/nsn/5305-00-195-9595

Thre	ead Class:
2a	
Thr	ead Direction:
Rigł	nt-hand
Thre	ead Length:
Betv	ween 0.271 inches and 0.281 inches
Fas	tener Length:
0.40	06 inches
Hea	d Style:
Fillis	ster
Hea	d Diameter:
Betv	ween 0.166 inches and 0.183 inches
Неа	d Height:
Betv	ween 0.072 inches and 0.079 inches
Firs	t Diameter From Head:
0.11	2 inches
Sec	ond Diameter From Head:
Betv	veen 0.081 inches and 0.084 inches
Dist	ance From Largest Bearing Surface Of Head To End Of First Diameter:
Betv	ween 0.271 inches and 0.281 inches
Dist	ance From Largest Bearing Surface Of Head To End Of Second Diameter:
0.40	06 inches
Inte	rnal Drive Style:
Slot	
Thr	ead Diameter:
0.11	2 inches
Thre	eady Qty Per Inch (tpi):
40	
Min	. Tensile Strength (psi):
800	00 pounds per square inch
Exte	ernally Relieved Body Diameter Quantity:
2	
Spe	cial Features:
Firs	t diameter from head is threaded portion
Mat	erial:
Stai	nless steel
Mat	erial Specification:
66 f	ederal standard single material response
Sur	face Treatment:
Pas	sivate
Thre	ead Series Designator:
Unc	

Externally Relieved Body Screw - Page 2 of 2



Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0