

View Online at <https://aerobasegroup.com/nsn/5305-00-195-9616>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

Between 0.125 inches and 0.157 inches

Fastener Length:

Between 0.406 inches and 0.438 inches

Head Style:

Pan no. 2

Head Diameter:

Between 0.155 inches and 0.167 inches

Head Height:

Between 0.045 inches and 0.053 inches

First Diameter From Head:

0.058 inches

Distance From Largest Bearing Surface Of Head To End Of First Diameter:

0.281 inches

Internal Drive Style:

Slot

Thread Diameter:

0.086 inches

Thready Qty Per Inch (tpi):

56

Min. Tensile Strength (psi):

55000 pounds per square inch

Externally Relieved Body Diameter Quantity:

1

Material Specification:

Qq-s-634 federal specification 1st material response or qq-s-634 federal specification 2nd material response or qq-s-634 federal specification 3rd material response or qq-s-634 federal specification 4th material response or qq-s-634 federal specification 5th material response or qq-s-634 federal specification 6th material response or qq-s-634 federal specification 7th material response or qq-s-634 federal specification 8th material response or qq-s-634 federal specification 9th material response or qq-s-634 federal specification 10th material response or qq-s-634 federal specification 11th material response or qq-s-634 federal specification 12th material response or qq-s-634 federal specification 13th material response or qq-s-634 federal specification 14th material response or qq-s-634 federal specification 15th material response or qq-s-634 federal specification 16th material response or qq-s-634 federal specification 17th material response or qq-s-630 federal specification 18th material response or qq-s-631 federal specification 18th material response or qq-s-637 federal specification 18th material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Mil-f-14072, finish no. -262 military specification single treatment response

Thread Series Designator:

Unc

Shelf Life:

Fig:

A003b0

Mil-std (military Standard):

Mil-f-14072 spec.