NSN 5305-00-196-4335

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-196-4335 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.169 inches and 0.250 inches **Fastener Length:** Between 0.219 inches and 0.250 inches **Head Style:** Pan **Head Diameter:** Between 0.205 inches and 0.219 inches **Head Height:** Between 0.070 inches and 0.080 inches **Internal Drive Style:** Torque set **Thread Diameter:** 0.112 inches Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: Between 248.0 brinell standard and 341.0 brinell standard **Screw Material:** Iron alloy 660 **Screw Material Specification:** Ams 5737 assn standard single material response **Screw Surface Treatment: Screw Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unjc **Specification Data:** 80205-nas1100 professional/industrial association standard Shelf Life: N/a **Unit Of Measure:**

Demilitarization:

Passivate

No

NSN 5305-00-196-4335 Machine Screw - Page 2 of 2



Fiig:

A500d0