

NSN 5305-00-197-6364 Close Tolerance Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-00-197-6364 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.547 inches and 0.697 inches

**Fastener Length:** 

Between 1.640 inches and 1.687 inches

**Head Style:** 

Flat countersunk undercut

**Head Diameter:** 

Between 0.629 inches and 0.633 inches

**Head Height:** 

Between 0.088 inches and 0.090 inches

**Grip Diameter:** 

Between 0.3110 inches and 0.3120 inches

**Internal Drive Style:** 

High-torque

**Thread Diameter:** 

0.312 inches

**Grip Length:** 

Between 0.990 inches and 1.010 inches

Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

180000 pounds per square inch

Hardness Rating:

40.0 rockwell c and 43.0 rockwell c

**Countersink Angle:** 

100.0 degrees

**Surface Finish:** 

32.0 microinches grip

**Special Features:** 

Furnished w/1 preformed packing

Material:

Steel

**Surface Treatment:** 

Cadmium

**Surface Treatment Specification:** 

Nas 672 assn standard single treatment response

**Thread Series Designator:** 

Unf

## NSN 5305-00-197-6364

Close Tolerance Screw - Page 2 of 2



_					
c	hο	JIF.		.ife:	
J			_	.II C.	

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0