

View Online at <https://aerobasegroup.com/nsn/5305-00-202-0399>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

Between 1.380 inches and 1.700 inches

Fastener Length:

Between 3.180 inches and 3.220 inches

Head Style:

Hexagon

Head Height:

Between 0.455 inches and 0.483 inches

Width Between Flats:

Between 1.100 inches and 1.125 inches

Shank Unthreaded Hole Diameter:

0.124 inches first hole and 0.129 inches first hole

Thread Diameter:

0.750 inches

Thready Qty Per Inch (tpi):

10

Min. Tensile Strength (psi):

150000 pounds per square inch

Hardness Rating:

32.0 rockwell c and 38.0 rockwell c

Minimum Yield Strength:

120000 pounds per square inch

Distance From Head Largest Bearing Surface To Shank Hole Center:

1.790 inches first hole and 1.830 inches first hole

Material:

Steel

Material Specification:

Sae gr 8 assn standard single material response

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416, type 2, cl 3 federal specification all treatment responses

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0