NSN 5305-00-202-0607

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-202-0607 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.220 inches **Fastener Length:** 0.620 inches **Head Style:** Pan **Head Diameter:** Between 0.205 inches and 0.219 inches **Head Height:** Between 0.070 inches and 0.080 inches **First Diameter From Head:** 0.080 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.400 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.112 inches Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 80000 pounds per square inch **Externally Relieved Body Diameter Quantity: Product Name:** Navy special project Material: Stainless steel **Material Specification:** Qq-s-763, 300 series federal specification single material response or 66, 300 series federal standard single material response or comp 16-18 or 18-8 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Mil-f-14072 finish e300 military specification single treatment response **Thread Series Designator:**

N/a

Unc

Shelf Life:

NSN 5305-00-202-0607

Externally Relieved Body Screw - Page 2 of 2



Unit Of Measure:	U	In	it	Of	Measure:
------------------	---	----	----	----	----------

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-f-14072 spec.