NSN 5305-00-202-1584

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-202-1584 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.250 inches **Fastener Length:** 0.620 inches **Head Style:** Fillister **Head Diameter:** Between 0.208 inches and 0.226 inches **Head Height:** Between 0.118 inches and 0.132 inches **First Diameter From Head:** 0.100 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.370 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 **Special Features:** Cone point 120 degree Material: Steel comp 303 or steel comp 303se **Material Specification:** Astm a582 assn standard all material responses **Surface Treatment: Passivate Surface Treatment Specification:** Pd3330 fscm 87557 mfr ref single treatment response **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:**

--

NSN 5305-00-202-1584

Externally Relieved Body Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0