NSN 5305-00-205-5606

Externally Relieved Body Screw - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5305-00-205-5606 |
|---|
| Thread Class: |
| 3a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| 0.219 inches |
| Fastener Length: |
| 0.594 inches |
| Head Style: |
| Flat chamfer |
| Head Diameter: |
| Between 0.221 inches and 0.226 inches |
| Head Height: |
| Between 0.074 inches and 0.086 inches |
| First Diameter From Head: |
| 0.086 inches |
| Distance From Largest Bearing Surface Of Head To End Of First Diameter: |
| 0.375 inches |
| Internal Drive Style: |
| Offset cruciform (torque set) |
| Thread Diameter: |
| 0.138 inches |
| Thready Qty Per Inch (tpi): |
| 32 |
| Min. Tensile Strength (psi): |
| 140000 pounds per square inch |
| Externally Relieved Body Diameter Quantity: |
| 1 |
| Material: |
| Iron alloy 660 |
| Material Specification: |
| Ams5732 assn standard single material response |
| Surface Treatment: |
| Passivate |
| Thread Series Designator: |
| Unc |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |

No

NSN 5305-00-205-5606

Externally Relieved Body Screw - Page 2 of 2



Fiig:

A003b0