NSN 5305-00-206-1576

Shoulder Screw - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5305-00-206-1576

2a Thread Direction: Right-hand Thread Length: 0.250 inches Fastener Length: 0.500 inches Head Style: Flat chamfer Head Diameter: 0.500 inches Head Height: 0.094 inches Shoulder Diameter: 0.243 inches first shoulde Shoulder Length: 0.250 inches first shoulde Shoulder Length: 0.250 inches first shoulde Shoulder Length: 0.250 inches first shoulde Internal Drive Style: Slot Thread Diameter: 0.190 inches Thready Qty Per Inch (tp 24 Shoulder Shape: Round first shoulder Material: Steel comp 303 Surface Treatment: Passivate Thread Series Designate Unc		t shoulder	
Right-hand Thread Length: 0.250 inches Fastener Length: 0.500 inches Head Style: Flat chamfer Head Diameter: 0.500 inches Head Height: 0.094 inches Shoulder Diameter: 0.243 inches first shoulde Shoulder Length: 0.250 inches first shoulde Internal Drive Style: Slot Thread Diameter: 0.190 inches Thready Qty Per Inch (tp 24 Shoulder Shape: Round first shoulder Material: Steel comp 303 Surface Treatment: Passivate Thread Series Designate		tshoulder	
Thread Length: 0.250 inches Fastener Length: 0.500 inches Head Style: Flat chamfer Head Diameter: 0.500 inches Head Height: 0.094 inches Shoulder Diameter: 0.243 inches first shoulde Shoulder Length: 0.250 inches first shoulde Internal Drive Style: Slot Thread Diameter: 0.190 inches Thready Qty Per Inch (tp 24 Shoulder Shape: Round first shoulder Material: Steel comp 303 Surface Treatment: Passivate Thread Series Designate		tshoulder	
0.250 inches Fastener Length: 0.500 inches Head Style: Flat chamfer Head Diameter: 0.500 inches Head Height: 0.094 inches Shoulder Diameter: 0.243 inches first shoulde Shoulder Length: 0.250 inches first shoulde Internal Drive Style: Slot Thread Diameter: 0.190 inches Thready Qty Per Inch (tp 24 Shoulder Shape: Round first shoulder Material: Steel comp 303 Surface Treatment: Passivate Thread Series Designate		tshoulder	
Fastener Length: 0.500 inches Head Style: Flat chamfer Head Diameter: 0.500 inches Head Height: 0.094 inches Shoulder Diameter: 0.243 inches first shoulde Shoulder Length: 0.250 inches first shoulde Internal Drive Style: Slot Thread Diameter: 0.190 inches Thready Qty Per Inch (tp 24 Shoulder Shape: Round first shoulder Material: Steel comp 303 Surface Treatment: Passivate Thread Series Designate		tshoulder	
0.500 inches Head Style: Flat chamfer Head Diameter: 0.500 inches Head Height: 0.094 inches Shoulder Diameter: 0.243 inches first shoulder Shoulder Length: 0.250 inches first shoulder Internal Drive Style: Slot Thread Diameter: 0.190 inches Thready Qty Per Inch (tp 24 Shoulder Shape: Round first shoulder Material: Steel comp 303 Surface Treatment: Passivate Thread Series Designate		t shoulder	
Head Style: Flat chamfer Head Diameter: 0.500 inches Head Height: 0.094 inches Shoulder Diameter: 0.243 inches first shoulde Shoulder Length: 0.250 inches first shoulde Internal Drive Style: Slot Thread Diameter: 0.190 inches Thready Qty Per Inch (tp 24 Shoulder Shape: Round first shoulder Material: Steel comp 303 Surface Treatment: Passivate Thread Series Designate		t shoulder	
Flat chamfer Head Diameter: 0.500 inches Head Height: 0.094 inches Shoulder Diameter: 0.243 inches first shoulde Shoulder Length: 0.250 inches first shoulde Internal Drive Style: Slot Thread Diameter: 0.190 inches Thready Qty Per Inch (tp 24 Shoulder Shape: Round first shoulder Material: Steel comp 303 Surface Treatment: Passivate Thread Series Designate		t shoulder	
Head Diameter: 0.500 inches Head Height: 0.094 inches Shoulder Diameter: 0.243 inches first shoulde Shoulder Length: 0.250 inches first shoulde Internal Drive Style: Slot Thread Diameter: 0.190 inches Thready Qty Per Inch (tp 24 Shoulder Shape: Round first shoulder Material: Steel comp 303 Surface Treatment: Passivate Thread Series Designate		t shoulder	
0.500 inches Head Height: 0.094 inches Shoulder Diameter: 0.243 inches first shoulde Shoulder Length: 0.250 inches first shoulde Internal Drive Style: Slot Thread Diameter: 0.190 inches Thready Qty Per Inch (tp 24 Shoulder Shape: Round first shoulder Material: Steel comp 303 Surface Treatment: Passivate Thread Series Designate		t shoulder	
Head Height: 0.094 inches Shoulder Diameter: 0.243 inches first shoulde Shoulder Length: 0.250 inches first shoulde Internal Drive Style: Slot Thread Diameter: 0.190 inches Thready Qty Per Inch (tp 24 Shoulder Shape: Round first shoulder Material: Steel comp 303 Surface Treatment: Passivate Thread Series Designate		t shoulder	
0.094 inches Shoulder Diameter: 0.243 inches first shoulde Shoulder Length: 0.250 inches first shoulde Internal Drive Style: Slot Thread Diameter: 0.190 inches Thready Qty Per Inch (tp 24 Shoulder Shape: Round first shoulder Material: Steel comp 303 Surface Treatment: Passivate Thread Series Designate		t shoulder	
Shoulder Diameter: 0.243 inches first shoulde Shoulder Length: 0.250 inches first shoulde Internal Drive Style: Slot Thread Diameter: 0.190 inches Thready Qty Per Inch (tp 24 Shoulder Shape: Round first shoulder Material: Steel comp 303 Surface Treatment: Passivate Thread Series Designate		t shoulder	
0.243 inches first shoulde Shoulder Length: 0.250 inches first shoulde Internal Drive Style: Slot Thread Diameter: 0.190 inches Thready Qty Per Inch (tp 24 Shoulder Shape: Round first shoulder Material: Steel comp 303 Surface Treatment: Passivate Thread Series Designate		t shoulder	
Shoulder Length: 0.250 inches first shoulde Internal Drive Style: Slot Thread Diameter: 0.190 inches Thready Qty Per Inch (tp 24 Shoulder Shape: Round first shoulder Material: Steel comp 303 Surface Treatment: Passivate Thread Series Designate		t shoulder	
0.250 inches first shoulde Internal Drive Style: Slot Thread Diameter: 0.190 inches Thready Qty Per Inch (tp 24 Shoulder Shape: Round first shoulder Material: Steel comp 303 Surface Treatment: Passivate Thread Series Designate	r		
Internal Drive Style: Slot Thread Diameter: 0.190 inches Thready Qty Per Inch (tp 24 Shoulder Shape: Round first shoulder Material: Steel comp 303 Surface Treatment: Passivate Thread Series Designate	r		
Slot Thread Diameter: 0.190 inches Thready Qty Per Inch (tp 24 Shoulder Shape: Round first shoulder Material: Steel comp 303 Surface Treatment: Passivate Thread Series Designate			
Thread Diameter: 0.190 inches Thready Qty Per Inch (tp 24 Shoulder Shape: Round first shoulder Material: Steel comp 303 Surface Treatment: Passivate Thread Series Designate			
0.190 inches Thready Qty Per Inch (tp 24 Shoulder Shape: Round first shoulder Material: Steel comp 303 Surface Treatment: Passivate Thread Series Designate			
Thready Qty Per Inch (tp 24 Shoulder Shape: Round first shoulder Material: Steel comp 303 Surface Treatment: Passivate Thread Series Designate			
24 Shoulder Shape: Round first shoulder Material: Steel comp 303 Surface Treatment: Passivate Thread Series Designate			
Shoulder Shape: Round first shoulder Material: Steel comp 303 Surface Treatment: Passivate Thread Series Designate	i):		
Round first shoulder Material: Steel comp 303 Surface Treatment: Passivate Thread Series Designate			
Material: Steel comp 303 Surface Treatment: Passivate Thread Series Designate			
Steel comp 303 Surface Treatment: Passivate Thread Series Designate			
Surface Treatment: Passivate Thread Series Designate			
Passivate Thread Series Designate			
Thread Series Designate			
Linc	r:		
One			
Shelf Life:			
N/a			
Unit Of Measure:			
 Demilitarization:			
No			
Fiig:			