

View Online at <https://aerobasegroup.com/nsn/5305-00-206-4010>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 1.000 inches and 1.188 inches

**Fastener Length:**

Between 1.563 inches and 1.625 inches

**Head Style:**

Hexagon

**Head Height:**

Between 0.226 inches and 0.243 inches

**Width Between Flats:**

Between 0.551 inches and 0.562 inches

**Shank Unthreaded Hole Diameter:**

0.128 inches first hole

**Thread Diameter:**

0.375 inches

**Thready Qty Per Inch (tpi):**

24

**Min. Tensile Strength (psi):**

69000 pounds per square inch

**Hardness Rating:**

100.0 rockwell b

**Minimum Yield Strength:**

55000 pounds per square inch

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

1.497 inches first hole

**Material:**

Steel

**Material Specification:**

Sae gr 2 assn standard single material response

**Thread Series Designator:**

Unf

**Specification Or Standard:**

2 type and 10p style

**Departure From Cited Designator:**

As modified by drilled hole in shank and fastener length

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0