NSN 5305-00-206-5507

N/a

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-206-5507 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.297 inches and 0.312 inches **Fastener Length:** 0.938 inches **Head Style:** Hexagon **Head Height:** Between 0.172 inches and 0.190 inches Width Between Flats: Between 0.367 inches and 0.375 inches **Hole Diameter:** 0.062 inches First Diameter From Head: Between 0.180 inches and 0.184 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.625 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.250 inches **Hole Quantity:** 1 **Hole Type:** Drilled Thready Qty Per Inch (tpi): 20 **Hole Configuration Style:** Hexagon flats **Externally Relieved Body Diameter Quantity:** 1 Material: Steel comp 1015 or steel comp 1016 or steel comp 1017 or steel comp 1018 or steel comp 1019 or steel comp 1020 or steel comp 1023 or steel comp 1025 or steel comp 1211 or steel comp 1212 or steel comp 1213 **Surface Treatment:** Cadmium **Thread Series Designator:** Unc Shelf Life:

NSN 5305-00-206-5507

Externally Relieved Body Screw - Page 2 of 2



ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A003b0