## NSN 5305-00-206-7538

Externally Relieved Body Screw - Page 1 of 1



| View Online at https://aerobasegroup.com/nsn/5305-00-206-7538                |
|--|
| Thread Class:  |
| 2a   |
| Thread Direction:  |
| Right-hand   |
| Thread Length:   |
| 0.425 inches   |
| Fastener Length:   |
| 0.500 inches   |
| Head Style:  |
| Flat chamfer   |
| Head Diameter:   |
| Between 0.372 inches and 0.375 inches  |
| Head Height:   |
| 0.125 inches   |
| First Diameter From Head:  |
| Between 0.172 inches and 0.182 inches  |
| Distance From Largest Bearing Surface Of Head To End Of First Diameter:      |
| 0.075 inches   |
| Internal Drive Style:  |
| Slot   |
| Thread Diameter:   |
| 0.250 inches   |
| Thready Qty Per Inch (tpi):  |
| 20   |
| Externally Relieved Body Diameter Quantity:                                  |
| 1  |
| Material:  |
| Copper alloy 462 or copper alloy 464 or copper alloy 482 or copper alloy 485 |
| Material Specification:  |
| Qq-b-637 federal specification all material responses                        |
| Thread Series Designator:  |
| Unc  |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |
| Demilitarization:  |
| No   |
| Fiig:  |
| A003b0   |