

View Online at <https://aerobasegroup.com/nsn/5305-00-206-8828>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 1.062 inches and 1.126 inches

**Fastener Length:**

Between 1.172 inches and 1.204 inches

**Head Style:**

Headless (setscrew)

**Head Height:**

Between 0.359 inches and 0.391 inches

**Width Between Flats:**

Between 0.609 inches and 0.641 inches

**Point Length:**

Between 0.046 inches and 0.078 inches

**Internal Drive Style:**

W/o internal drive

**Thread Diameter:**

0.625 inches

**Thready Qty Per Inch (tpi):**

18

**Min. Tensile Strength (psi):**

150000 pounds per square inch

**Hardness Rating:**

33.0 rockwell c and 38.0 rockwell c

**Criticality Code Justification:**

Feat

**Point Chamfer Angle:**

Between 89.0 degrees and 91.0 degrees

**Special Features:**

Unthd portion of shank 0.094 in. Lg, 0.549 in. Dia

**Material:**

Steel comp 4130

**Material Specification:**

Mil-s-6758, cond c military specification single material response

**Surface Treatment:**

Cadmium and chromate

**Surface Treatment Specification:**

Qq-p-416 type 2 cl 3 federal specification all treatment responses

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-s-6758 spec.