Externally Relieved Body Screw - Page 1 of 2



3a         Thread Direction:         Right-hand         Thread Length:         0.125 inches         Fastener Length:         0.306 inches         Head Style:         Flat chamfer         Head Diameter:         0.250 inches         Head Height:         0.062 inches         Head Height:         0.062 inches         First Diameter From Head:         0.124 inches         Second Diameter From Head:         0.124 inches         Distance From Largest Bearing Surface Of Head To End Of First Diameter:         0.025 inches         Distance From Largest Bearing Surface Of Head To End Of Second Diameter:         0.126 inches         Internal Drive Style:         Cross recess type 1         Thread Diameter:         0.138 inches         Features Provided:         Casehardened         Thready Qty Per Inch (tpi):         40         Externally Relieved Body Diameter Quantity:         2         Special Features:         Plating removed from pilot         Material:         Steel         Surface Treatment:         Nickel     <	Т	hread Class:
Right-hand   Thread Length:   0.125 inches   Fastener Length:   0.306 inches   Head Style:   Flat chamfer   Head Diameter:   0.250 inches   Head Height:   0.062 inches   Head Height:   0.062 inches   First Diameter From Head:   0.124 inches   Second Diameter From Head:   0.094 inches   Distance From Largest Bearing Surface Of Head To End Of First Diameter:   0.025 inches   Distance From Largest Bearing Surface Of Head To End Of Second Diameter:   0.126 inches   Internal Drive Style:   Cross recess type 1   Thread Diameter:   0.138 inches   Features Provided:   Casehardened   Thready Qty Per Inch (tpi):   40   Externally Relieved Body Diameter Quantity:   2   Special Features:   Plating removed from pilot   Material:   Steel   Surface Treatment:   Nickel	3	a
Tread Length: 0.125 inches Fastener Length: 0.306 inches Head Style: Flat chamfer Head Diameter: 0.250 inches Head Height: 0.052 inches First Diameter From Head: 0.062 inches First Diameter From Head: 0.054 inches Second Diameter From Head: 0.094 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.025 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 0.025 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 0.025 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 0.156 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.138 inches Features Provided: Casehardened Thready Qty Per Inch (tpi): 40 Externally Relieved Body Diameter Quantity: 2 Special Features: Plating removed from pilot Material: Steel Surface Treatment: Nickel Thread Series Designator:	т	hread Direction:
0.125 inches Fastener Length: 0.306 inches Head Style: Flat chamfer Head Diameter: 0.250 inches Head Height: 0.062 inches First Diameter From Head: 0.062 inches First Diameter From Head: 0.0124 inches Second Diameter From Head: 0.094 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.025 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 0.025 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 0.025 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 0.025 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 0.025 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 0.136 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.138 inches Features Provided: Casehardened Thread Diameter: 0.138 inches Features Provided: Casehardened Thread Second Diameter Quantity: 2 Special Features: Plating removed from pilot Material: Steel Surface Treatment: Nickel Thread Second Designator:	R	ight-hand
Transmission         Restener Length:         0.306 inches         Head Style:         Flat chamfer         Head Diameter:         0.250 inches         Head Height:         0.062 inches         First Diameter From Head:         0.124 inches         Second Diameter From Head:         0.094 inches         Distance From Largest Bearing Surface Of Head To End Of First Diameter:         0.025 inches         Distance From Largest Bearing Surface Of Head To End Of Second Diameter:         0.025 inches         Distance From Largest Bearing Surface Of Head To End Of Second Diameter:         0.025 inches         Internal Drive Style:         Cross recess type 1         Thread Diameter:         0.138 inches         Features Provided:         Casehardened         Thready Qty Per Inch (tpi):         40         Externally Relieved Body Diameter Quantity:         2         Special Features:         Plating removed from pilot         Material:         Steel         Surface Treatment:         Nickel         Thread Series Designator:	Т	hread Length:
0.306 inches Head Style: Flat chamfer Head Diameter: 0.250 inches Head Height: 0.052 inches First Diameter From Head: 0.062 inches Second Diameter From Head: 0.094 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.025 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 0.025 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 0.025 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 0.156 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.138 inches Features Provided: Casehardened Thready Qty Per Inch (tpi): 40 Externally Relieved Body Diameter Quantity: 2 Special Features: Plating removed from pilot Material: Steel Surface Treatment: Nickel	0	.125 inches
Head Style:         Flat chamfer         Head Diameter:         0.250 inches         Head Height:         0.062 inches         First Diameter From Head:         0.124 inches         Second Diameter From Head:         0.094 inches         Distance From Largest Bearing Surface Of Head To End Of First Diameter:         0.025 inches         Distance From Largest Bearing Surface Of Head To End Of Second Diameter:         0.126 inches         Internal Drive Style:         Cross recess type 1         Thread Diameter:         0.138 inches         Features Provided:         Casehardened         Thready Qty Per Inch (tpi):         40         Externally Relieved Body Diameter Quantity:         2         Special Features:         Plating removed from pilot         Material:         Steel         Surface Treatment:         Nickel	F	astener Length:
Flat chamfer Head Diameter: 0.250 inches Head Height: 0.062 inches First Diameter From Head: 0.124 inches Second Diameter From Head: 0.094 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.025 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 0.025 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 0.156 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.138 inches Features Provided: Casehardened Thready Qty Per Inch (tpi): 40 Externally Relieved Body Diameter Quantity: 2 Special Features: Plating removed from pilot Material: Steel Surface Treatment: Nickel	0	.306 inches
Head Diameter: 0.250 inches Head Height: 0.062 inches First Diameter From Head: 0.124 inches Second Diameter From Head: 0.094 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.025 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 0.156 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.138 inches Features Provided: Casehardened Thready Qty Per Inch (tpi): 40 Externally Relieved Body Diameter Quantity: 2 Special Features: Plating removed from pilot Material: Steel Surface Treatment: Nickel	Н	ead Style:
0.250 inches Head Height: 0.062 inches First Diameter From Head: 0.124 inches Second Diameter From Head: 0.094 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.025 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 0.025 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 0.156 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.138 inches Features Provided: Casehardened Thready Qty Per Inch (tpi): 40 Externally Relieved Body Diameter Quantity: 2 Special Features: Plating removed from pilot Material: Steel Surface Treatment: Nickel	F	lat chamfer
Head Height: 0.062 inches First Diameter From Head: 0.124 inches Second Diameter From Head: 0.094 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.025 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 0.126 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.138 inches Features Provided: Casehardened Thready Qty Per Inch (tpi): 40 Externally Relieved Body Diameter Quantity: 2 Special Features: Plating removed from pilot Material: Steel Surface Treatment: Nickel	Н	ead Diameter:
0.062 inches First Diameter From Head: 0.124 inches Second Diameter From Head: 0.094 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.025 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 0.156 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.138 inches Features Provided: Casehardened Thready Qty Per Inch (tpi): 40 Externally Relieved Body Diameter Quantity: 2 Special Features: Plating removed from pilot Material: Steel Surface Treatment: Nickel	0	.250 inches
First Diameter From Head: 0.124 inches Second Diameter From Head: 0.094 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.025 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 0.126 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.138 inches Features Provided: Casehardened Thready Qty Per Inch (tpi): 40 Externally Relieved Body Diameter Quantity: 2 Special Features: Plating removed from pilot Material: Steel Surface Treatment: Nickel	Н	lead Height:
0.124 inches Second Diameter From Head: 0.094 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.025 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 0.156 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.138 inches Features Provided: Casehardened Thready Qty Per Inch (tpi): 40 Externally Relieved Body Diameter Quantity: 2 Special Features: Plating removed from pilot Material: Steel Surface Treatment: Nickel	0	.062 inches
Second Diameter From Head: 0.094 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.025 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 0.126 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.138 inches Features Provided: Casehardened Thready Qty Per Inch (tpi): 40 Externally Relieved Body Diameter Quantity: 2 Special Features: Plating removed from pilot Material: Steel Surface Treatment: Nickel Thread Series Designator:	F	irst Diameter From Head:
0.094 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.025 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 0.156 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.138 inches Features Provided: Casehardened Thready Qty Per Inch (tpi): 40 Externally Relieved Body Diameter Quantity: 2 Special Features: Plating removed from pilot Material: Steel Surface Treatment: Nickel	0	.124 inches
Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.025 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 0.156 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.138 inches Features Provided: Casehardened Thready Qty Per Inch (tpi): 40 Externally Relieved Body Diameter Quantity: 2 Special Features: Plating removed from pilot Material: Steel Surface Treatment: Nickel	S	econd Diameter From Head:
0.025 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 0.156 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.138 inches Features Provided: Casehardened Thready Qty Per Inch (tpi): 40 Externally Relieved Body Diameter Quantity: 2 Special Features: Plating removed from pilot Material: Steel Surface Treatment: Nickel	0	.094 inches
Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 0.156 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.138 inches Features Provided: Casehardened Thready Qty Per Inch (tpi): 40 Externally Relieved Body Diameter Quantity: 2 Special Features: Plating removed from pilot Material: Steel Surface Treatment: Nickel	D	istance From Largest Bearing Surface Of Head To End Of First Diameter:
0.156 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.138 inches Features Provided: Casehardened Thready Qty Per Inch (tpi): 40 Externally Relieved Body Diameter Quantity: 2 Special Features: Plating removed from pilot Material: Steel Surface Treatment: Nickel Thread Series Designator:	0	.025 inches
Internal Drive Style: Cross recess type 1 Thread Diameter: 0.138 inches Features Provided: Casehardened Thready Qty Per Inch (tpi): 40 Externally Relieved Body Diameter Quantity: 2 Special Features: Plating removed from pilot Material: Steel Surface Treatment: Nickel	D	istance From Largest Bearing Surface Of Head To End Of Second Diameter:
Cross recess type 1 Thread Diameter: 0.138 inches Features Provided: Casehardened Thready Qty Per Inch (tpi): 40 Externally Relieved Body Diameter Quantity: 2 Special Features: Plating removed from pilot Material: Steel Surface Treatment: Nickel Thread Series Designator:	0	.156 inches
Thread Diameter: 0.138 inches Features Provided: Casehardened Thready Qty Per Inch (tpi): 40 Externally Relieved Body Diameter Quantity: 2 Special Features: Plating removed from pilot Material: Steel Surface Treatment: Nickel	lr	nternal Drive Style:
0.138 inches Features Provided: Casehardened Thready Qty Per Inch (tpi): 40 Externally Relieved Body Diameter Quantity: 2 Special Features: Plating removed from pilot Material: Steel Surface Treatment: Nickel Thread Series Designator:	С	ross recess type 1
Features Provided:   Casehardened   Thready Qty Per Inch (tpi):   40   Externally Relieved Body Diameter Quantity:   2   Special Features:   Plating removed from pilot   Material:   Steel   Surface Treatment:   Nickel   Thread Series Designator:	Т	hread Diameter:
Casehardened Thready Qty Per Inch (tpi): 40 Externally Relieved Body Diameter Quantity: 2 Special Features: Plating removed from pilot Material: Steel Steel Surface Treatment: Nickel Thread Series Designator:	0	.138 inches
Thready Qty Per Inch (tpi): 40 Externally Relieved Body Diameter Quantity: 2 Special Features: Plating removed from pilot Material: Steel Surface Treatment: Nickel Thread Series Designator:	F	eatures Provided:
40 Externally Relieved Body Diameter Quantity: 2 Special Features: Plating removed from pilot Material: Steel Surface Treatment: Nickel Thread Series Designator:	С	asehardened
Externally Relieved Body Diameter Quantity: 2 Special Features: Plating removed from pilot Material: Steel Surface Treatment: Nickel Thread Series Designator:	Т	hready Qty Per Inch (tpi):
2 Special Features: Plating removed from pilot Material: Steel Surface Treatment: Nickel Thread Series Designator:	4	0
Special Features: Plating removed from pilot Material: Steel Surface Treatment: Nickel Thread Series Designator:	E	xternally Relieved Body Diameter Quantity:
Plating removed from pilot Material: Steel Surface Treatment: Nickel Thread Series Designator:	2	
Material: Steel Surface Treatment: Nickel Thread Series Designator:	S	pecial Features:
Steel Surface Treatment: Nickel Thread Series Designator:	Ρ	lating removed from pilot
Surface Treatment: Nickel Thread Series Designator:	N	laterial:
Nickel Thread Series Designator:	S	teel
Thread Series Designator:	S	urface Treatment:
	N	lickel
Unf	т	hread Series Designator:
	U	nf

Externally Relieved Body Screw - Page 2 of 2



Unit Of Measure:

---

Demilitarization:

No

Fiig:

A003b0