Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-206-9861

| Thread Class: | |
|---|--|
| 3a | |
| Thread Direction: | |
| Right-hand | |
| Thread Length: | |
| 0.187 inches | |
| Fastener Length: | |
| 0.500 inches | |
| Head Style: | |
| Flat chamfer | |
| Head Diameter: | |
| 0.312 inches | |
| Head Height: | |
| 0.188 inches | |
| First Diameter From Head: | |
| 0.097 inches | |
| Distance From Largest Bearing Surface Of Head To End Of First Diameter: | |
| 0.312 inches | |
| Internal Drive Style: | |
| Slot | |
| Thread Diameter: | |
| 0.138 inches | |
| Thready Qty Per Inch (tpi): | |
| 32 | |
| Hardness Rating: | |
| 82.6 rockwell b | |
| Minimum Yield Strength: | |
| 22000 pounds per square inch | |
| Externally Relieved Body Diameter Quantity: | |
| 1 | |
| Material: | |
| Steel comp 303 | |
| Material Specification: | |
| Qq-s-763 federal specification single material response | |
| Thread Series Designator: | |
| Unc | |
| Shelf Life: | |
| N/a | |
| Unit Of Measure: | |
| | |
| Demilitarization: | |
| No | |

NSN 5305-00-206-9861

Externally Relieved Body Screw - Page 2 of 2

Fiig: A003b0

