Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-207-2265

| Thread Classe |
|---|
| Thread Class: 2a |
| |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| 0.438 inches |
| Fastener Length: |
| 0.562 inches |
| Head Style: |
| Fillister |
| Head Diameter: |
| Between 0.292 inches and 0.313 inches |
| Head Height: |
| Between 0.107 inches and 0.123 inches |
| Hole Diameter: |
| 0.046 inches |
| First Diameter From Head: |
| Between 0.145 inches and 0.149 inches |
| Distance From Largest Bearing Surface Of Head To End Of First Diameter: |
| 0.125 inches |
| Internal Drive Style: |
| Slot |
| Thread Diameter: |
| 0.190 inches |
| Hole Quantity: |
| 1 |
| Ноје Туре: |
| Drilled |
| Thready Qty Per Inch (tpi): |
| 32 |
| Hole Configuration Style: |
| Round |
| Externally Relieved Body Diameter Quantity: |
| 1 |
| Material: |
| Steel comp 1020 or steel comp 1119 |
| Material Specification: |
| Astm a108 assn standard 1st material response or qq-s-637 federal specification 2nd material response |
| Thread Series Designator: |
| Unf |
| Shelf Life: |
| N/a |
| |

Externally Relieved Body Screw - Page 2 of 2



Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0