## NSN 5305-00-207-6958

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-207-6958 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.625 inches **Fastener Length:** 4.250 inches **Head Style:** Round **Head Diameter:** Between 0.240 inches and 0.260 inches **Head Height:** Between 0.091 inches and 0.103 inches **First Diameter From Head:** 0.138 inches **Second Diameter From Head:** 0.094 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.312 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 0.359 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 2 Material: Steel comp 1020 or steel comp 1213 **Material Specification:** Qq-s-630 federal specification 1st material response or qq-s-631 federal specification 1st material response or qq-s-634 federal specification 1st material response or qq-s-633 federal specification 2nd material response **Surface Treatment:** Cadmium **Thread Series Designator:** Unc Shelf Life:

--

N/a

**Unit Of Measure:** 

## NSN 5305-00-207-6958

Externally Relieved Body Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0