NSN 5305-00-207-7464

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-207-7464 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.652 inches **Fastener Length:** Between 0.657 inches and 0.688 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.150 inches and 0.172 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.086 inches Thready Qty Per Inch (tpi): 56 Min. Tensile Strength (psi): 80000 pounds per square inch **Countersink Angle:** Between 80.0 degrees and 82.0 degrees **Screw Material:** Steel comp 430 or steel comp 302 **Screw Material Specification:** Qq-s-763 federal specification 1st material response or mil-s-7720 military specification 2nd material response **Screw Surface Treatment: Passivate Screw Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unc **Specification Or Standard:** 1 type and 2s style Shelf Life: N/a **Unit Of Measure: Demilitarization:**

No Fiig:

A500d0

NSN 5305-00-207-7464

Machine Screw - Page 2 of 2



Mil-std (military Standard):

Mil-s-7720 spec.