## NSN 5305-00-207-8185

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-207-8185 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.125 inches **Fastener Length:** Between 0.275 inches and 0.285 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.364 inches and 0.368 inches **Head Height:** Between 0.347 inches and 0.357 inches **First Diameter From Head:** Between 0.186 inches and 0.196 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.150 inches and 0.160 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 150000 pounds per square inch Hardness Rating: 34.0 rockwell c and 38.0 rockwell c **Externally Relieved Body Diameter Quantity:** 1 **Special Features:** 2 drilled holes in head Material: Steel comp 8630 **Material Specification:** Mil-s-6050 military specification single material response **Thread Series Designator:** Unf Shelf Life: N/a **Unit Of Measure:** 

--

## NSN 5305-00-207-8185

Externally Relieved Body Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-6050 spec.