NSN 5305-00-208-1583

N/a

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-208-1583 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.188 inches **Fastener Length:** 0.625 inches **Head Style:** Binding **Head Diameter:** 0.321 inches **Head Height:** 0.115 inches **First Diameter From Head:** 0.164 inches **Second Diameter From Head:** Between 0.097 inches and 0.103 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.047 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 0.438 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.164 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 2 **Special Features:** Red gloss enamel Material: Stainless steel **Surface Treatment:** Enamel head **Surface Treatment Specification:** Usa-72-53 military specification single treatment response head and usa-3-1 no. 105 military specification single treatment response head **Thread Series Designator:** Unc Shelf Life:

NSN 5305-00-208-1583

Externally Relieved Body Screw - Page 2 of 2



| Demilitarization: | |
|-------------------|--|
| No | |
| Fiig: | |
| A003b0 | |

Unit Of Measure:

Mil-std (military Standard): spec.