## NSN 5305-00-208-4455

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-208-4455 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.609 inches and 0.641 inches **Fastener Length:** 2.125 inches **Head Style:** Pan no. 2 **Head Diameter:** Between 0.382 inches and 0.408 inches **Head Height:** Between 0.125 inches and 0.156 inches **First Diameter From Head:** Between 0.185 inches and 0.190 inches **Second Diameter From Head:** Between 0.141 inches and 0.146 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.109 inches and 0.141 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 1.500 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 2 Material: Steel comp 1212 **Material Specification:** Qq-s-633 federal specification single material response **Surface Treatment:** Zinc **Surface Treatment Specification:** Qq-z-325, type 2, cl 3 federal specification single treatment response **Thread Series Designator:** Unf Shelf Life:

N/a

## NSN 5305-00-208-4455

Externally Relieved Body Screw - Page 2 of 2



			ure:	

--

Demilitarization:

No

Fiig:

A003b0