## NSN 5305-00-208-7381

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-208-7381 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.210 inches and 0.230 inches **Fastener Length:** Between 0.590 inches and 0.610 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.292 inches and 0.312 inches **Head Height:** 0.141 inches **First Diameter From Head:** 0.190 inches **Second Diameter From Head:** Between 0.130 inches and 0.133 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.040 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 0.380 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 2 Material: Steel comp 303 or steel comp 304 or steel comp 305 **Surface Treatment: Passivate Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure: Demilitarization:** 

No

## NSN 5305-00-208-7381

Externally Relieved Body Screw - Page 2 of 2



Fiig:

A003b0