Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-210-2063

Thread Class:	
3a	
Sa Thread Direction:	
Right-hand	
Thread Length:	
Between 1.250 inches and 1.560 inches	
Fastener Length:	
Between 7.312 inches and 7.438 inches	
Head Style:	
Flat chamfer	
Head Diameter:	
Between 0.550 inches and 0.562 inches	
Head Height:	
Between 0.368 inches and 0.375 inches	
Hole Diameter:	
0.064 inches	
Internal Drive Style:	
Hexagon	
Thread Diameter:	
0.375 inches	
Width Across Flats:	
0.312 inches	
Hole Quantity:	
4	
Hole Type:	
Drilled	
Thready Qty Per Inch (tpi):	
16	
Min. Tensile Strength (psi):	
160000 pounds per square inch	
Hardness Rating:	
36.0 rockwell c and 45.0 rockwell c	
Minimum Yield Strength:	
130000 pounds per square inch	
Hole Configuration Style:	
Round	
Material:	
Steel	
Material Specification:	
66 federal standard single material response	
Surface Treatment:	
Zinc	

NSN 5305-00-210-2063

Socket Head Cap Screw - Page 2 of 2



Surface Treatment Specification:

Qq-z-325, type 2, cl 3 federal specification single treatment response

Thread Series Designator:

Unc

Specification Or Standard:

1 type

Departure From Cited Designator:

As modified by head hole configuration and thread length and fastener length

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0