

NSN 5305-00-210-2089 Socket Head Cap Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-00-210-2089 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.984 inches and 1.031 inches **Fastener Length:** Between 1.859 inches and 1.906 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.303 inches and 0.312 inches **Head Height:** Between 0.185 inches and 0.190 inches **Hole Diameter:** 0.047 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.190 inches Width Across Flats: 0.156 inches **Hole Quantity: Hole Type:** Drilled Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 160000 pounds per square inch

Hardness Rating:

36.0 rockwell c and 45.0 rockwell c

Minimum Yield Strength:

130000 pounds per square inch

Hole Configuration Style:

Round internal hexagon

Material:

Steel

Material Specification:

66 federal standard single material response

Surface Treatment:

Zinc

NSN 5305-00-210-2089

Socket Head Cap Screw - Page 2 of 2



Surface Treatment Spec	ific	ation:
------------------------	------	--------

Qq-z-325, type 2, cl 3 federal specification single treatment response

Thread Series Designator:

Unc

Specification Or Standard:

1 type

Departure From Cited Designator:

As modified by no. Of drilled holes and thd class

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0