

View Online at <https://aerobasegroup.com/nsn/5305-00-211-5508>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.045 inches and 0.125 inches

Fastener Length:

Between 0.095 inches and 0.125 inches

Head Style:

Flat chamfer

Head Diameter:

Between 0.176 inches and 0.183 inches

Head Height:

Between 0.108 inches and 0.112 inches

Hole Diameter:

0.036 inches

Internal Drive Style:

Hexagon

Thread Diameter:

0.112 inches

Width Across Flats:

Between 0.094 inches and 0.095 inches

Hole Quantity:

2

Hole Type:

Drilled

Thready Qty Per Inch (tpi):

40

Min. Tensile Strength (psi):

180000 pounds per square inch

Hardness Rating:

38.0 rockwell c and 45.0 rockwell c

Minimum Yield Strength:

30000 pounds per square inch

Hole Configuration Style:

Round internal hexagon

Material:

Steel comp 302 or steel comp 304 or steel comp 305 or steel comp 316 or steel comp 384 or steel

Material Specification:

66 federal standard 1st material response or 66 federal standard 2nd material response or 66 federal standard 3rd material response or 66 federal standard 4th material response or 66 federal standard 5th material response or astm-a493 aisi xm-7 assn standard 6th material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, type 1, cl 2 federal specification single treatment response

Thread Series Designator:

Unjc

Specification Data:

80205-nas1352 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0