NSN 5305-00-211-8142

Thumbscrew - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-211-8142

Thread Class:
2a
Thread Direction:
Right-hand
Thread Length:
Between 0.265 inches and 0.297 inches
Fastener Length:
0.719 inches
Head Style:
Knurled no. 1
Head Diameter:
Between 0.307 inches and 0.317 inches
Head Height:
Between 0.172 inches and 0.204 inches
First Diameter From Head:
Between 0.090 inches and 0.100 inches
Distance From Largest Bearing Surface Of Head To End Of First Diameter:
Between 0.422 inches and 0.454 inches
Point Style:
Cone
Thread Diameter:
0.138 inches
Thready Qty Per Inch (tpi):
32
Externally Relieved Body Diameter Quantity:
1
Material:
Steel comp 303
Material Specification:
Astm a582 assn standard single material response
Surface Treatment:
Passivate
Special Test Features:
Special quality control testing
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Test Data Document:
81349-mil-p-23199 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Thread Series Designator:
Unc
Reference Number Differentiating Characteristics:

As differentiated by material which must conform to ships parts control center special quality control provisions

NSN 5305-00-211-8142

Thumbscrew - Page 2 of 2



	Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0