

View Online at <https://aerobasegroup.com/nsn/5305-00-211-9226>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.534 inches and 0.601 inches

**Fastener Length:**

Between 0.732 inches and 0.779 inches

**Head Style:**

Flat countersunk

**Head Diameter:**

Between 0.698 inches and 0.762 inches

**Grip Diameter:**

Between 0.3733 inches and 0.3742 inches

**Shank Unthreaded Hole Diameter:**

0.106 inches first hole

**Internal Drive Style:**

High-torque

**Thread Diameter:**

0.375 inches

**Grip Length:**

Between 0.178 inches and 0.198 inches

**Thread Qty Per Inch (tpi):**

24

**Min. Tensile Strength (psi):**

220000 pounds per square inch

**Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

0.4398 inches first hole and 0.471 inches first hole

**Material:**

Steel

**Material Specification:**

Sps-m-107 fscm 56878 mfr ref single material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Nas 672 assn standard 1st treatment response or mil-c-8837 type 2 cl 2 military specification 2nd treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-c-8837 spec.