Socket Head Cap Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-00-211-9260



Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.845 inches and 0.875 inches
Fastener Length:
0.875 inches
Head Style:
Flat chamfer
Head Diameter:
Between 0.303 inches and 0.312 inches
Head Height:
Between 0.185 inches and 0.190 inches
Hole Diameter:
0.047 inches
Internal Drive Style:
Hexagon
Thread Diameter:
0.190 inches
Width Across Flats:
Between 0.156 inches and 0.159 inches
Hole Quantity:
6
Hole Type:
Drilled
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
180000 pounds per square inch
Hardness Rating:
38.0 rockwell c and 45.0 rockwell c
Minimum Yield Strength:
155000 pounds per square inch
Hole Configuration Style:
Round internal hexagon
Material:
Steel
Surface Treatment:
Cadmium
Surface Treatment Specification:

Qq-p-416 type 2 cl 2 federal specification single treatment response

NSN 5305-00-211-9260

Socket Head Cap Screw - Page 2 of 2



Thread Series Designator:

Unrc

Specification Data:

80205-nas1352 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0