NSN 5305-00-213-8741

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-213-8741 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.339 inches and 0.500 inches **Fastener Length:** Between 0.470 inches and 0.500 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.365 inches and 0.375 inches **Head Height:** Between 0.244 inches and 0.250 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.250 inches Width Across Flats: Between 0.187 inches and 0.190 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 80000 pounds per square inch Hardness Rating: 80.0 rockwell b Minimum Yield Strength: 30000 pounds per square inch Material: Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316 **Material Specification:** 66 federal standard all material responses **Surface Treatment:** Oxide **Surface Treatment Specification:** Mil-c-13924 cl 4 military specification single treatment response **Thread Series Designator:** Unf **Specification Or Standard:** 6 type Shelf Life:

N/a

NSN 5305-00-213-8741

Socket Head Cap Screw - Page 2 of 2



П	Init	7 1+	Measure:
u	,,,,,	v	wicasuic.

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-13924 spec.