Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-213-8884

Thread Class:
2a
Thread Direction:
Right-hand
Thread Length:
Between 0.292 inches and 0.332 inches
Fastener Length:
Between 0.968 inches and 1.000 inches
Head Style:
Pan
Head Diameter:
Between 0.473 inches and 0.492 inches
Head Height:
Between 0.162 inches and 0.175 inches
First Diameter From Head:
Between 0.178 inches and 0.188 inches
Distance From Largest Bearing Surface Of Head To End Of First Diameter:
Between 0.636 inches and 0.708 inches
Internal Drive Style:
Cross recess type 1
Thread Diameter:
0.250 inches
Thready Qty Per Inch (tpi):
28
Externally Relieved Body Diameter Quantity:
1
Material:
Steel comp 302 or steel comp 303
Material Specification:
Qq-s-763 federal specification 1st material response or astm a582 assn standard 2nd material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Mil-f-14072 finish e300 military specification single treatment response
Thread Series Designator:
Unf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

## NSN 5305-00-213-8884

Externally Relieved Body Screw - Page 2 of 2



**Fiig:** A003b0

Mil-std (military Standard):

Mil-f-14072 spec.