## NSN 5305-00-217-2446

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-217-2446 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.469 inches and 0.500 inches **Fastener Length:** Between 0.531 inches and 0.562 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.359 inches and 0.385 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 960 pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Screw Material:** Steel comp 1010 **Screw Material Specification:** Qq-s-671 federal specification single material response **Screw Surface Treatment:** Cadmium **Screw Surface Treatment Specification:** Qq-p-416, type 1, cl 3 federal specification single treatment response **Thread Series Designator:** Unf **Specification Data:** 81348-ff-s-92 government specification and 88044-an507/canceled/ government standard **Departure From Cited Designator:** As modified by material and surface treatment Shelf Life: N/a **Unit Of Measure:** 

No

**Demilitarization:** 

## **NSN 5305-00-217-2446** Machine Screw - Page 2 of 2



Fiig:

A500d0