## NSN 5305-00-218-4687

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-218-4687 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 1.830 inches and 2.031 inches **Fastener Length:** Between 1.984 inches and 2.031 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.735 inches and 0.750 inches **Head Height:** Between 0.492 inches and 0.500 inches **Hole Diameter:** 0.125 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.500 inches Width Across Flats: Between 0.375 inches and 0.379 inches **Hole Quantity:** 2 **Hole Type:** Drilled Thready Qty Per Inch (tpi): 13 Min. Tensile Strength (psi): 80000 pounds per square inch Hardness Rating: 80.0 rockwell b **Hole Configuration Style:** Round internal hexagon **Criticality Code Justification:** Test Material: Steel comp 304 **Surface Treatment: Passivate** 

**Special Test Features:** 

Special quality control testing

## NSN 5305-00-218-4687

Socket Head Cap Screw - Page 2 of 2



## **Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

## **Test Data Document:**

Fiig: A003b0

81349-mil-p-23199 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

environmental and performance requirements and test conditions that are shown as typical, average,
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No