NSN 5305-00-218-4864

Assembled Washer Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-218-4864 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.658 inches and 0.780 inches **Fastener Length:** Between 0.720 inches and 0.780 inches **Head Style:** Pan no. 2 **Head Diameter:** Between 0.256 inches and 0.270 inches **Head Height:** Between 0.072 inches and 0.082 inches Washer Quantity: **Internal Drive Style:** Slot **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): 32 **Primary Washer Outside Diameter:** Between 0.270 inches and 0.285 inches **Primary Washer Style:** Flat external teeth **Primary Washer Material Thickness:** Between 0.014 inches and 0.020 inches **Material Specification:** Aisi assn standard all material responses primary washer **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, type 2, cl 3 federal specification all treatment responses **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:**

Demilitarization:

No

NSN 5305-00-218-4864

Assembled Washer Screw - Page 2 of 2



Fiig:

A003b0