NSN 5305-00-223-1983

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-223-1983

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.230 inches and 0.250 inches
Fastener Length:
Between 0.620 inches and 0.630 inches
Head Style:
Flat chamfer
Head Diameter:
Between 0.419 inches and 0.438 inches
Head Height:
Between 0.213 inches and 0.219 inches
Shoulder Diameter:
0.3085 inches first shoulder and 0.3105 inches first shoulder
Shoulder Length:
0.370 inches first shoulder and 0.380 inches first shoulder
Internal Drive Style:
Hexagon
Thread Diameter:
0.250 inches
Width Across Flats:
Between 0.156 inches and 0.159 inches
Thready Qty Per Inch (tpi):
20
Min. Tensile Strength (psi):
160000 pounds per square inch
Hardness Rating:
32.0 rockwell c and 43.0 rockwell c
Minimum Yield Strength:
145000 pounds per square inch
Shoulder Shape:
Round first shoulder
Material:
Steel
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:

--

NSN 5305-00-223-1983

Shoulder Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0