Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-223-2004

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.148 inches and 0.200 inches
Fastener Length:
Between 0.190 inches and 0.200 inches
Head Style:
Flat chamfer
Head Diameter:
Between 0.154 inches and 0.161 inches
Head Height:
Between 0.095 inches and 0.099 inches
Hole Diameter:
0.023 inches
Internal Drive Style:
Hexagon
Thread Diameter:
0.099 inches
Width Across Flats:
Between 0.078 inches and 0.079 inches
Hole Quantity:
4
Hole Type:
Drilled
Thready Qty Per Inch (tpi):
48
Min. Tensile Strength (psi):
80000 pounds per square inch
Hardness Rating:
80.0 rockwell b
Minimum Yield Strength:
30000 pounds per square inch
Hole Configuration Style:
Round internal hexagon
Material:
Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316
Material Specification:
66 federal standard all material responses Surface Treatment:
Passivate

NSN 5305-00-223-2004

Socket Head Cap Screw - Page 2 of 2



Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0