## NSN 5305-00-224-0953

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-224-0953 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.356 inches and 0.438 inches **Fastener Length:** Between 0.406 inches and 0.438 inches **Head Style:** Pan **Head Diameter:** Between 0.205 inches and 0.219 inches **Head Height:** Between 0.070 inches and 0.080 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.112 inches Thready Qty Per Inch (tpi): 40 Min. Tensile Strength (psi): 160000 pounds per square inch **Screw Material:** Steel comp 8630 or steel comp 4037 **Screw Material Specification:** Mil-s-6050 military specification 1st material response or ams 6300 assn standard 2nd material response **Screw Surface Treatment:** Cadmium and chromate **Screw Surface Treatment Specification:** Qq-p-416, type 2, cl 3 federal specification single treatment response **Special Features:** Paint area black color no. 37038 federal standard 595 and furnished wylon washer **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure: Demilitarization:** No

Fiig:

A500d0

## NSN 5305-00-224-0953

Machine Screw - Page 2 of 2



Mil-std (military Standard):

Mil-s-6050 spec.