

View Online at <https://aerobasegroup.com/nsn/5305-00-224-1092>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

Between 0.419 inches and 0.500 inches

Fastener Length:

Between 0.469 inches and 0.500 inches

Head Style:

Pan no. 2

Head Diameter:

Between 0.256 inches and 0.270 inches

Head Height:

Between 0.058 inches and 0.068 inches

Washer Quantity:

1

Internal Drive Style:

Slot

End Application:

Radar set, lightweight 3d (an/tps-59); generator, 15kw, diesel, military; generator, 30kw, diesel, military standard family; generator, 60kw, diesel, military standard family; generator set, diesel engine, 100kw, pu-495; generator set, 3kw, 60hz, skid-mtd, mep-061b; generator set, 30kw, 60 hz, skid mounted (3id) (mep-007a); generator set, tact quiet, 60kw, 400hz, mep-816a; generator set, 60kw, 60 hz, skid-mounted (2id) (mep-006a)

Thread Diameter:

0.112 inches

Thready Qty Per Inch (tpi):

40

Primary Washer Outside Diameter:

Between 0.220 inches and 0.230 inches

Primary Washer Style:

Flat external teeth

Primary Washer Material Thickness:

Between 0.012 inches and 0.020 inches

Material:

Steel

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416, type 2, class 3 federal specification single treatment response

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0