

View Online at <https://aerobasegroup.com/nsn/5305-00-224-9243>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

Between 0.794 inches and 0.875 inches

Fastener Length:

Between 0.844 inches and 0.875 inches

Head Style:

Pan

Head Diameter:

Between 0.205 inches and 0.219 inches

Head Height:

Between 0.070 inches and 0.080 inches

Locking Feature:

Patch threads or pellet threads or strip threads

Internal Drive Style:

Cross recess type 1

End Application:

W/s: helicopter, seahawk h-60; helicopter, carrier based asw, sh-60f; helicopter, search and rescue, hh-60h; helicopter, uscg search and rescue, hh-60j; aircraft, f-16; aircraft, intruder a-6e; aircraft, prowler ea-6b; helicopter, lamps mark iii, sh-60b

Thread Diameter:

0.112 inches

Thready Qty Per Inch (tpi):

40

Min. Tensile Strength (psi):

60000 pounds per square inch

Material:

Steel

Material Specification:

Qq-s-637 federal specification single material response or 66 federal standard single material response

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416, type 2, class 3 federal specification all treatment responses

Thread Series Designator:

Unc

Specification Or Standard:

3 type and 9c style

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0