

View Online at <https://aerobasegroup.com/nsn/5305-00-224-9243>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.794 inches and 0.875 inches

**Fastener Length:**

Between 0.844 inches and 0.875 inches

**Head Style:**

Pan

**Head Diameter:**

Between 0.205 inches and 0.219 inches

**Head Height:**

Between 0.070 inches and 0.080 inches

**Locking Feature:**

Patch threads or pellet threads or strip threads

**Internal Drive Style:**

Cross recess type 1

**End Application:**

W/s: helicopter, seahawk h-60; helicopter, carrier based asw, sh-60f; helicopter, search and rescue, hh-60h; helicopter, uscg search and rescue, hh-60j; aircraft, f-16; aircraft, intruder a-6e; aircraft, prowler ea-6b; helicopter, lamps mark iii, sh-60b

**Thread Diameter:**

0.112 inches

**Thready Qty Per Inch (tpi):**

40

**Min. Tensile Strength (psi):**

60000 pounds per square inch

**Material:**

Steel

**Material Specification:**

Qq-s-637 federal specification single material response or 66 federal standard single material response

**Surface Treatment:**

Cadmium and chromate

**Surface Treatment Specification:**

Qq-p-416, type 2, class 3 federal specification all treatment responses

**Thread Series Designator:**

Unc

**Specification Or Standard:**

3 type and 9c style

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0