NSN 5305-00-224-9451

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-224-9451 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.234 inches and 0.266 inches **Fastener Length:** Between 0.564 inches and 0.586 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.484 inches and 0.516 inches **Head Height:** Between 0.075 inches and 0.085 inches **Shoulder Diameter:** 0.248 inches first shoulder and 0.250 inches first shoulder **Shoulder Length:** 0.320 inches first shoulder and 0.330 inches first shoulder **Internal Drive Style:** Slot **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 32 **Shoulder Shape:** Round first shoulder Material: Steel comp 303 **Material Specification:** Qq-s-764, cond a federal specification single material response **Surface Treatment: Passivate Surface Treatment Specification:** Mil-f-14072, finish no. E300, type 2 military specification single treatment response **Thread Series Designator:** Unf Shelf Life: N/a **Unit Of Measure:**

No

Demilitarization:

NSN 5305-00-224-9451

Shoulder Screw - Page 2 of 2



Fiig:

A003b0

Mil-std (military Standard):

Mil-f-14072 spec.