NSN 5305-00-225-3848

Machine Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-00-225-3848



Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

Between 0.804 inches and 0.875 inches

Fastener Length:

0.875 inches

Head Style:

Flat countersunk

Head Diameter:

Between 0.442 inches and 0.507 inches

Internal Drive Style:

Cross recess type 1

End Application:

W/s: truck, utility, cargo troop carrier, 5/4-ton w/e (m998); aircraft, stratolifter c-135; tank, combat, ft, 120mm gun (m1a1); singars system family

Thread Diameter:

0.250 inches

Thready Qty Per Inch (tpi):

28

Min. Tensile Strength (psi):

62000 pounds per square inch

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Screw Material:

Aluminum alloy 2024

Screw Material Specification:

Qq-a-225/6 federal specification single material response

Screw Surface Treatment:

Anodize

Screw Surface Treatment Specification:

Mil-a-8625 military specification single treatment response

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A500d0

NSN 5305-00-225-3848

Machine Screw - Page 2 of 2

Mil-std (military Standard):

Mil-a-8625 spec.

