NSN 5305-00-225-6208

Machine Screw - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5305-00-225-6208 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.429 inches and 0.578 inches **Fastener Length:** Between 1.641 inches and 1.688 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.447 inches and 0.507 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 62000 pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Screw Material:** Aluminum alloy 2024 **Screw Material Specification:** Qq-a-225/6 federal specification single material response or qq-a-430 federal specification single material response **Screw Surface Treatment:** Anodize and anodize **Screw Surface Treatment Specification:** Mil-a-8625, type 1 military specification 1st treatment response and mil-a-8625, type 2 military specification 2nd treatment response **Thread Series Designator:** Unf Shelf Life: N/a **Unit Of Measure: Demilitarization:** No

Fiig: A500d0

Mil-std (military Standard):

Mil-a-8625 spec.