## NSN 5305-00-225-6403

Machine Screw - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5305-00-225-6403 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 1.042 inches and 1.125 inches **Fastener Length:** 1.125 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.670 inches and 0.762 inches **Internal Drive Style:** Cross recess type 1 **End Application:** W/s: support equipment, f-4 aircraft; support equipment, a-10 aircraft; support equipment, f-15 aircraft; support equipment, f-16 aircraft; simulator f-16; aircraft, f-16; support equipment, f-111 aircraft; support equipment, b-1 aircraft **Thread Diameter:** 0.375 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 60000 pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Screw Material:** Steel comp 1010 **Screw Material Specification:** Qq-s-630 federal specification single material response or qq-s-631 federal specification single material response or qq-s-634 federal specification single material response **Screw Surface Treatment Specification:** Qq-p-416 type 2 cl 3 federal specification single treatment response **Thread Series Designator:** Unf Shelf Life: N/a **Unit Of Measure: Demilitarization:** 

No Fiig:

A500d0